

**SUPERBRAK**

# SOLID SKID STEER TYRES



- Puncture-proof tyres - maintenance-free
- Long life span up to five times that of pneumatic tyres
- Blowouts made redundant - Danger of accidents eliminated
- Elimination of downtime & operational delays due to tyre-related issues
- Zero repair costs & reduced overheads normally associated with pneumatic tyres

# SUPERTRAK SOLID SKID STEER TYRES



SSK-SM



SSK-01

- Recommended for applications where punctures are a recurring problem
- Abrasion resistant tread for use on hard improved surfaces
- Sidewall apertures for shock absorption & comfort

- Stable Ride
- Mounted on heavy-duty wheels for direct fit with no special mounting equipment required
- Cost efficient & Environment friendly as compared to foam filled tyres



SSK-02 (2R-20)



SSK-03 (4R-19)

## TECHNICAL SPECIFICATIONS

Size	Rim	Pattern		O.D.		S.W.		Load Capacity@10 Km/h		Replaces Pneumatic Tyre
				mm	inch	mm	inch	lbs	kg	
23x7-10	5.00	SSK-01	1R-14	583	22.95	178	7.01	5082	2310	5.70-12
30x8-16	6.00	SSK-01	-	780	30.71	195	7.70	7260	3300	10-16.5
30x9-16	6.00	SSK-02	2R-40	750	29.53	205	8.07	6490	2950	10-16.5
30x9-16 SM	6.00	SSK-SM	-	755	29.72	220	8.66	8580	3900	10-16.5
30x10-16	6.00	SSK-03	4R-19	745	29.33	235	9.25	5500	2500	10-16.5
33x9-16	6.00	SSK-02	1R-20	850	33.47	230	9.06	9570	4350	12-16.5
33x9-16 SM	6.00	SSK-SM	-	850	33.47	230	9.06	11240	5110	12-16.5
30x10-18	7.00	SSK-04	2R-36	745	29.33	250	9.84	6490	2950	10-16.5
33x12-20	7.50	SSK-02	2R-20	835	32.87	271	10.71	8800	4000	12-16.5
36x12-20										Under Development

